

FIBER OPTIC GYROSCOPE

VG191AD / VG191AD-MS



PERFORMANCE

Input range	°/s	300	for info
Bias, RMS	°/h	1	Allan variance min
ARW	°/√h	0.012	white noise PSD
Bandwidth	kHz	0.6	
SF, RMS	%	0.02	day-to-day
Magnetic response	°/h/Gauss	3 / 0.05	typical

ELECTRICAL INTERFACE

Initialization	s	0.03	
Powering	W	0.5	+5V
Data rate	kHz	8	24-bit data
Baud rate	kBd	921.6	RS422, asynchronous

ENVIRONMENT

Operating temperature	°C	-40...+70	
Endurance temperature	°C	-55...+85	> 2 h, non-operating
Vibration, RMS	g	18	20 Hz... 2000 Hz
Shocks	g	750	1 ms half-sine

PHYSICAL PARAMETERS

Dimensions	mm	Ø24 x 48	ISO 2768-m
Weight	gram	30 / 45	
Housing		Al alloy / μ-metal	IP67

RELIABILITY

MTBF / Lifetime	yr	15	humidity conditions applied
-----------------	----	----	-----------------------------

fizoptika.com

Datasheet

May 2023

Fizoptika Malta reserves the right to change the design or specifications at any time without prior notice. All pictures shown are for illustration purpose only. The actual product may vary due to the ongoing product enhancement.